



<b>PRINT</b>	
Printing Method	Monochrome Laser Beam Printing
Print Speed (A4)	23ppm
Print Resolution	600 x 600dpi
Print Quality with Image Refinement Technology	1 200 x 1 200dpi (equivalent)
Warm-Up Time (From Power On)	13.5s
First Print Out Time (FPOT) A4	6.0s
Recovery Time (From Sleep Mode)	2.0s
Print Language	UFR II LT
Print Margin	5mm-top, bottom, left and right (Other sizes than Envelope) 10mm-top, bottom, left and right (Envelope)
<b>COPY</b>	
Copy Speed (A4)	23ppm

Copy Resolution	600 x 600dpi	
First Copy Time (FCOT) A4	9.0s	
Maximum Number of Copies	999 copies	
Reduce / Enlargement	25 - 400% in 1% increments	
Copy Features	Memory Sort, 2 on 1, 4 on 1, ID Card Copy	
<b>SCAN</b>		
Scan Type	Colour Contact Image Sensor	
Scan Resolution	Optical	Up to 600 x 600dpi
	Driver Enhanced	Up to 9 600 x 9 600dpi
Maximum Scan Size	Platen Glass	Up to 216 x 297mm
Scan Speed (*2)	Platen Glass	3.0s per sheet (mono) 4.0s per sheet (colour)
	ADF (A4)	20ipm / 15ipm (mono / colour)
Colour Depth	24bit	
Pull Scan	Yes, USB	
Push Scan (Scan To PC) with MF Scan Utility	Yes, USB	
Scan to Cloud	Yes, MF Scan Utility	
Scan Driver Compatibility	TWAIN, WIA, ICA	
<b>FAX</b>		
Modem Speed	33.6 Kbps	
Fax Resolution	200 x 400dpi	
Compression Method	MH, MR, MMR	
Memory Capacity (*3)	256 pages	
One-touch Dial	4 dials	
Coded Dials	100 dials	
Group Dials / Destinations	Maximum 103 dials / Maximum 50 destinations	
Sequential Broadcast	Maximum 114 destinations	

Duplex Fax (TX)	No	
Receive Mode	Fax Only, Manual, Answering Machine, Fax / Tel Auto Switch	
Memory Backup	Permanent Fax Memory Back-up	
Fax Features	Fax Forwarding*, Dual Access, Remote Reception, PC Fax (Transmission only), DRPD, ECM, Auto Redial, Fax Activity Reports, Fax Activity Result Reports, Fax Activity Management Reports *This function only supports forwarding to another fax machine.	
<b>PAPER HANDLING</b>		
Auto Document Feeder (ADF)	35 sheets (80g/m <sup>2</sup> )	
Available Paper Size for ADF	A4, B5, A5, B6, Letter, Legal (105 x 148mm to Maximum 216 x 356mm)	
Paper Input	Standard Cassette	250 sheets
	Multi-Purpose Tray	1 sheet
Paper Output (Based on 68g/m <sup>2</sup> )	100 sheets (face down)	
Paper Size	Standard Cassette	A4, B5, A5, Legal, Letter, Statement, Executive, Government Letter, Government Legal, Foolscap, Indian Legal Custom (76.2 x 210mm to Maximum 216 x 356mm)
	Multi-Purpose Tray	A4, B5, A5, Legal, Letter, Statement, Executive, Government Letter, Government Legal, Foolscap, Indian Legal Custom (76.2 x 127mm to Max. 216 x 356mm)
Paper Weight	Standard Cassette	60 to 163g/m <sup>2</sup>
	Multi-Purpose Tray	60 to 163g/m <sup>2</sup>
Paper Type	Plain, Heavy, Recycled, Color, Label, Index Card, Envelope	
<b>CONNECTIVITY &amp; SOFTWARE</b>		
Standard Interface	Wired	High-Speed USB 2.0

Mobile Printing Capability		
Compatible Operating Systems	Microsoft® Windows® 10 (32 / 64-bit), Windows® 8.1 (32 / 64-bit), Windows® 8 (32 / 64-bit), Windows® 7 (32 / 64-bit), Windows Vista® (32 / 64-bit), Mac OS X <sup>(*4)</sup> 10.6.8~, Linux <sup>(*4)</sup>	
Software Included	Printer driver, Fax driver, Scanner driver, MF Scan Utility, AddressBook Tool, Toner Status	
<b>GENERAL</b>		
Device Memory	128Mb	
Operational Panel	9.2cm Monochrome LCD Touch Screen	
Dimensions (W x D x H)	390 x 371 x 360mm (Cassette closed) 390 x 441 x 360mm (Cassette opened)	
Weight	11.4kg (without cartridge) 12.0kg (with cartridge)	
Power Consumption	Maximum	1 120W
	During Operation (Average)	420W
	During Standby (Average)	5.1W
	During Sleep (Average)	1.2W (USB connection)
Noise level <sup>(*5)</sup>	During Operation	Sound Pressure Level: 51.0dB Sound Power Level: 6.5dB
	During Standby	Sound Pressure Level: Inaudible <sup>(*6)</sup> Sound Power Level: 43dB
Operating Environment	Temperature: 10 - 30°C Humidity: 20 - 80% RH (no condensation)	
Power Requirement	AC 220 - 240V (±10%), 50 / 60Hz (±2Hz)	
Consumables <sup>(*7)</sup>	Toner (Standard)	Cartridge 337: 2 400 pages (bundled: 1 700 pages)
	Monthly Duty Cycle <sup>(*8)</sup>	15 000 pages

Specifications are subject to change without notice.

\*1 Legal refers to paper measuring 215.9 x 355.6mm.

\*2 Scanning with 300 x 300dpi resolution. The communication time

is not included.

- \*3 Based on ITU-T Chart ( standard mode)
- \*4 Drivers for Mac OS can be downloaded from the [here](#) website when available.
- \*5 Measured in accordance with ISO 7779, declared noise emission in accordance with ISO 9296.
- \*6 "Inaudible" indicates the sound pressure level of each bystander position is below the ISO 7779 absolute criteria for the background noise level.
- \*7 Declared yield in accordance with ISO / IEC 19752.
- \*8 Monthly Duty Cycle value provides a means for comparison of product robustness in relation to other Canon laser devices, and does not refer to actual maximum image output per month.

- 
- All prices above are inclusive of all taxes.
- 

---

Copyright © 2021 Canon India Pvt Ltd. All rights reserved.